

# Weightronic

## Precise Balance




- Large and bright LCD display with backlight
- User's selectable weight units up to 13 choices
- Auto zero tracking & Auto calibration
- Full tare function
- Counting accumulation function
- Enclosed W / adjustable feet, bubble level, dust cover, wind shield

### Specifications

MODEL	BE-300	BE-600	BE-1200	BE-3000
Capacity	300 g	600 g	1200 g	3000 g
Resolution	0.01 g	0.01 g	0.02 g	0.1g
Pan Size	Ø120 mm		125 x 150 mm	
Power	AC adaptor or 6 x AA batteries(option)			
Operating Temperature	-10 °C ~ 40 °C / 14 °F ~ 104 °F			
Relative Humidity	0 ~ 95%, non condensing			
Display	LCD, 7 segments, 6 digits, back light			
Communication	Built-in serial interface RS232C data output			

*Specifications subject to change for improvement without notice*



#### Weightronic Pty. Ltd.

1 Francis Oakes Way, West Pennant Hills, NSW 2125, Australia  
Tel: [61] (02) 9872 9678 Fax: [61] (02) 9872 9679

#### Weightronic Technology Ltd.

G/F., 141 Yee Kuk Street, Sham Shui Po, Kln., Hong Kong  
Tel : [852] 2381 8818 Fax: [852] 2391 9919  
E-mail: sales@weightronic.com  
Web Site: <http://www.weightronic.com>